

VILLACRYL STC HOT LIQUID

Creation date	07th November 2023	Version	2.0
Revision date			

2.2. Label elements

Hazard pictogram



Signal word

Danger

Hazardous substances

methyl methacrylate
2-Propenoic acid, 2-methyl-, 1,1'-(1,4-butanediyl) ester

Hazard statements

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing mist/vapours/spray.
P264	Wash hands and exposed parts of the body thoroughly after handling.
P280	Wear protective gloves.
P370+P378	In case of fire: Use powder extinguisher/sand/carbon dioxide to extinguish.
P403+P235	Store in a well-ventilated place. Keep cool.

2.3. Other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605. Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture.

Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
Index: 607-035-00-6 CAS: 80-62-6 EC: 201-297-1	methyl methacrylate	<95	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Skin Sens. 1, H317 STOT SE 3, H335	1, 2
CAS: 2082-81-7 EC: 218-218-1 Registration number: 01-2119967415-30-XXXX	2-Propenoic acid, 2-methyl-, 1,1'-(1,4-butanediyl) ester	>5	Skin Irrit. 2, H315 Skin Sens. 1B, H317 Eye Irrit. 2, H319 STOT SE 3, H335	

Notes

- Note D: Certain substances which are susceptible to spontaneous polymerisation or decomposition are generally placed on the market in a stabilised form. It is in this form that they are listed in Part 3 of Annex VI to Regulation (EC) No 1272/2008. However, such substances are sometimes placed on the market in a non-stabilised form. In this case, the supplier who places such a substance on the market must state on the label the name of the substance followed by the words "non-stabilised".

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

VILLACRYL STC HOT LIQUID

Creation date	07th November 2023	Version	2.0
Revision date			

2 A substance for which exposure limits are set.

Full text of all classifications and hazard statements is given in the section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Take care of your own safety. If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet. If unconscious, put the person in the stabilized (recovery) position on his side with his head slightly bent backwards and make sure that airways are free; never induce vomiting. If the person vomits by himself, make sure that the vomit is not inhaled. In life threatening conditions first of all provide resuscitation of the affected person and ensure medical assistance. Respiratory arrest - provide artificial respiration immediately. Cardiac arrest - provide indirect cardiac massage immediately.

If inhaled

Terminate the exposure immediately; move the affected person to fresh air. Protect the person against growing cold. Provide medical treatment if irritation, dyspnoea or other symptoms persist.

If on skin

Remove contaminated clothes. Wash the affected area with plenty of water, lukewarm if possible. Soap, soap solution or shampoo should be used if there is no skin injury. Provide medical treatment if skin irritation persists. Rinse skin with water or shower.

If in eyes

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. Rinsing should continue at least for 10 minutes. Provide medical treatment, specialized if possible.

If swallowed

Rinse out the mouth with water and provide 2-5 dL of water. Provide medical treatment if the person has any health problems.

4.2. Most important symptoms and effects, both acute and delayed

If inhaled

May cause respiratory irritation.

If on skin

May cause an allergic skin reaction.

If in eyes

Causes serious eye irritation.

If swallowed

Irritation, nausea.

4.3. Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, carbon dioxide, powder, water spray jet, water mist.

Unsuitable extinguishing media

Water - full jet.

5.2. Special hazards arising from the substance or mixture

In the event of fire, carbon monoxide, carbon dioxide and other toxic gases may arise. Inhalation of hazardous degradation (pyrolysis) products may cause serious health damage.

5.3. Advice for firefighters

Self-Contained Breathing Apparatus (SCBA) with a chemical protection suit only where personal (close) contact is likely. Use a self-contained breathing apparatus and full-body protective clothing. Closed containers with the product near the fire should be cooled with water. Do not allow run-off of contaminated fire extinguishing material to enter drains or surface and ground water.

VILLACRYL STC HOT LIQUID

Creation date	07th November 2023	Version	2.0
Revision date			

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Provide sufficient ventilation. Highly flammable liquid and vapour. Remove all ignition sources. Use personal protective equipment for work. Follow the instructions in the Sections 7 and 8. Do not inhale mist/vapours/spray. Prevent contact with skin and eyes.

6.2. Environmental precautions

Prevent contamination of the soil and entering surface or ground water.

6.3. Methods and material for containment and cleaning up

Spilled product should be covered with suitable (non-flammable) absorbing material (sand, diatomaceous earth, earth and other suitable absorption materials); to be contained in well closed containers and removed as per the Section 13. In the event of leakage of the substantial amount of the product, inform fire brigade and other competent bodies. After removal of the product, wash the contaminated site with plenty of water. Do not use solvents.

6.4. Reference to other sections

See the Section 7, 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Prevent formation of gases and vapours in flammable or explosive concentrations and concentrations exceeding the occupational exposure limits. The product should be used only in the areas where it is not in contact with open fire and other ignition sources. Use non-sparking tools. Use of antistatic clothes and footwear is recommended. Do not inhale mist/vapours/spray. Prevent contact with skin and eyes. No smoking. Contaminated work clothing should not be allowed out of the workplace. Wash hands and exposed parts of the body thoroughly after handling. Use only outdoors or in a well-ventilated area. Use personal protective equipment as per Section 8. Observe valid legal regulations on safety and health protection. Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Take action to prevent static discharges.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers in cold, dry and well ventilated areas designated for this purpose. Do not expose to sunlight. Store locked up. Keep container tightly closed. Keep cool.

Content	Packaging type	Material of package
40 ml	bottle	GL
200 ml	bottle	HDPE

Storage class 3 - Flammable liquids

Storage temperature min 5 °C, max 25 °C

The specific requirements or rules relating to the substance/mixture

Solvent vapours are heavier than air and accumulate especially near the floor where they may form an explosive mixture with the air.

7.3. Specific end use(s)

not available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

The mixture contains substances for which occupational exposure limits are set.

European Union

Commission Directive 2009/161/EU

Substance name (component)	Type	Value
methyl methacrylate (CAS: 80-62-6)	OEL 8 hours	50 ppm
	OEL 15 minutes	100 ppm

DNEL

2-Propenoic acid, 2-methyl-, 1,1'-(1,4-butanediyl) ester					
Workers / consumers	Route of exposure	Value	Effect	Value determination	Source
Workers	Inhalation	14.5 mg/m ³	Chronic effects systemic	Toxicity test	ECHA

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

VILLACRYL STC HOT LIQUID

Creation date	07th November 2023	Version	2.0
Revision date			

2-Propenoic acid, 2-methyl-, 1,1'-(1,4-butanediyl) ester					
Workers / consumers	Route of exposure	Value	Effect	Value determination	Source
Consumers	Inhalation	4.3 mg/m ³	Chronic effects systemic	Toxicity test	ECHA
Workers	Dermal	4.2 mg/kg bw/day	Chronic effects systemic	Toxicity test	ECHA
Consumers	Dermal	2.5 mg/kg bw/day	Chronic effects systemic	Toxicity test	ECHA
Consumers	Oral	2.5 mg/kg bw/day	Chronic effects systemic	Toxicity test	ECHA

methyl methacrylate					
Workers / consumers	Route of exposure	Value	Effect	Value determination	Source
Workers	Inhalation	348.4 mg/m ³	Chronic effects systemic	Toxicity test	ECHA
Workers	Inhalation	208 mg/m ³	Chronic effects local		ECHA
Workers	Inhalation	416 mg/m ³	Acute effects local	Toxicity test	ECHA
Workers	Dermal	13.67 mg/kg bw/day	Chronic effects systemic	Toxicity test	ECHA
Workers	Dermal	1.5 mg/cm ²	Chronic effects local	Toxicity test	ECHA
Workers	Dermal	1.5 mg/cm ²	Acute effects local	Toxicity test	ECHA
Consumers	Inhalation	74.3 mg/m ³	Chronic effects systemic	Toxicity test	ECHA
Consumers	Inhalation	104 mg/m ³	Chronic effects local	Toxicity test	ECHA
Consumers	Inhalation	208 mg/m ³	Acute effects local	Toxicity test	ECHA
Consumers	Dermal	8.2 mg/kg bw/day	Chronic effects systemic	Toxicity test	ECHA
Consumers	Dermal	1.5 mg/cm ²	Acute effects local	Toxicity test	ECHA
Consumers	Oral	8.2 mg/kg bw/day	Chronic effects systemic	Toxicity test	ECHA
Consumers	Dermal	1.5 mg/cm ²	Chronic effects local		ECHA

PNEC

2-Propenoic acid, 2-methyl-, 1,1'-(1,4-butanediyl) ester			
Route of exposure	Value	Value determination	Source
Drinking water	43.5 µg/l	Experimentally	ECHA
Water (intermittent release)	97.9 µg/l	Experimentally	ECHA
Marine water	4.35 µg/l	Experimentally	ECHA
Microorganisms in sewage treatment	20 mg/l	Experimentally	ECHA
Freshwater sediment	3.12 mg/kg of dry substance of sediment	Experimentally	ECHA
Sea sediments	312 µg/kg of dry substance	Experimentally	ECHA
Soil (agricultural)	573 µg/kg of dry substance	Experimentally	ECHA

methyl methacrylate			
Route of exposure	Value	Value determination	Source
Drinking water	940 µg/l	Experimentally	ECHA
Water (intermittent release)	690 µg/l	Experimentally	ECHA

VILLACRYL STC HOT LIQUID

Creation date	07th November 2023	Version	2.0
Revision date			

methyl methacrylate			
Route of exposure	Value	Value determination	Source
Marine water	94 mg/kg	Experimentally	ECHA
Microorganisms in sewage treatment	10 mg/l	Experimentally	ECHA
Freshwater sediment	10.2 mg/kg of dry substance of sediment	Experimentally	ECHA
Sea sediments	1.02 mg/kg of dry substance of sediment	Experimentally	ECHA
Soil (agricultural)	1.48 mg/kg of dry substance of soil	Experimentally	ECHA

8.2. Exposure controls

Follow the usual measures intended for health protection at work and especially for good ventilation. This can be achieved only by local suction or efficient general ventilation. If exposure limits cannot be observed in this mode, suitable protection of airways must be used. Do not eat, drink and smoke during work. Wash your hands thoroughly with water and soap after work and before breaks for a meal and rest.

Eye/face protection

Protective goggles.

Skin protection

Hand protection: Protective gloves resistant to the product. When choosing appropriate thickness, material and permeability of the gloves, observe recommendations of their particular manufacturer. Observe other recommendations of the manufacturer. Other protection: protective workwear. Contaminated skin should be washed thoroughly.

Respiratory protection

Halfmask with a filter against organic vapours or a self-contained breathing apparatus as appropriate if exposure limit values of substances are exceeded or in a poorly ventilated environment.

Thermal hazard

Data not available.

Environmental exposure controls

Observe usual measures for protection of the environment, see Section 6.2.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	liquid
Colour	colourless
Odour	Typical for methacrylic acid esters
Melting point/freezing point	-48.2 °C
Boiling point or initial boiling point and boiling range	>100 °C
Flammability	inflammable
Lower and upper explosion limit	
bottom	2.1 %
upper	12.5 %
Flash point	10 °C
Auto-ignition temperature	430 °C
Decomposition temperature	>50 °C
pH	data not available
Kinematic viscosity	data not available
Solubility in water	15.9 g/l
Partition coefficient n-octanol/water (log value)	1.38
Vapour pressure	38.7 hPa
Density and/or relative density	
Density	940 g/cm ³ (nanoform)

VILLACRYL STC HOT LIQUID

Creation date	07th November 2023	Version	2.0
Revision date			

Relative vapour density	>1 w 20oC
Particle characteristics	data not available
Form	liquid
data not available	

9.2. Other information
none

SECTION 10: Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable under normal conditions. The product is stable in normal conditions of use and storage. Liquid is stabilized by hydroquinone (CAS no. 123-31-9). Nevertheless, the occurrence of self-polymerization reaction is possible after the expiry date, if the storage temperature is exceeded significantly or in case of direct and strong influence of UV radiation

10.3. Possibility of hazardous reactions

Uncontrolled polymerization reaction in the presence of factors which initiate occurrence of free radicals. The polymerization reaction is exothermic (heat releasing) and in uncontrolled conditions proceed very vigorous.

10.4. Conditions to avoid

The product is stable and no degradation occurs under normal use. Protect against flames, sparks, overheating and against frost. The usual precautions used for chemical products should be respected. Keep away from temperatures exceeding 40°C, direct sunlight and heat sources.

10.5. Incompatible materials

Protect against strong acids and alkalis, as well as against oxidizing substances. Strong oxidants, substances that generate free radicals, reducing substances, heavy metal ions, heat sources

10.6. Hazardous decomposition products

Not developed under normal uses. Dangerous outcomes such as carbon monoxide and carbon dioxide are formed at high temperature and in fire.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Inhalation of solvent vapors above values exceeding exposure limits for working environment may result in acute inhalation poisoning, depending on the level of concentration and exposure time. No toxicological data is available for the mixture.

Acute toxicity

Based on available data the classification criteria are not met.

2-Propenoic acid, 2-methyl-, 1,1'-(1,4-butanediyl) ester								
Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex	Value determination	Source
Oral	LD ₅₀	OECD 401	10.066 mg/kg bw/day		Rat (Wistar)	F/M	Experimentally	ECHA
Oral	LD ₅₀	OECD 401	9.83 ml/kg bw		Rat (Wistar)	F/M	Experimentally	ECHA

methyl methacrylate								
Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex	Value determination	Source
Oral	LD ₅₀		7900 mg/kg		Rat (Rattus norvegicus)		Mortal	ECHA Dossier
Inhalation	LC ₅₀		29.8 mg/l	4 hours	Rat (Rattus norvegicus)			ECHA Dossier
Dermal	LD ₅₀	OECD 402	>5000 mg/kg	24 hours	Rabbit	M		ECHA Dossier

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

VILLACRYL STC HOT LIQUID

Creation date

07th November 2023

Revision date

Version

2.0

methyl methacrylate								
Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex	Value determination	Source
Oral	NOAEL		7900 mg/kg bw/day		Rat (Rattus norvegicus)		Mortal	ECHA
Inhalation	NOAEL		29.8 mg/l	4 hours	Rat (Rattus norvegicus)			ECHA Dossier
Dermal	NOAEL	OECD 402	5000 mg/kg		Rabbit			ECHA Dossier

Skin corrosion/irritation

Causes skin irritation.

methyl methacrylate					
Route of exposure	Result	Exposure time	Species	Value determination	Source
Dermal	Irritating	24 hours	Rabbit	Toxicity test	ECHA

Irritation

2-Propenoic acid, 2-methyl-, 1,1'-(1,4-butanediyl) ester						
Route of exposure	Result	Method	Exposure time	Species	Value determination	Source
Dermal	Not irritating	in vivo	24 hours	Rabbit (New Zealand White)	Experimentally	ECHA
Eye	Not irritating	OECD 405	72 hours	Rabbit (New Zealand White)	Experimentally	ECHA

methyl methacrylate						
Route of exposure	Result	Method	Exposure time	Species	Value determination	Source
Inhalation	Irritating					ECHA

Serious eye damage/irritation

Causes serious eye irritation.

methyl methacrylate				
Route of exposure	Result	Exposure time	Species	Source
Eye	Not sensitizing		Rabbit	ECHA

Respiratory or skin sensitisation

May cause an allergic skin reaction.

2-Propenoic acid, 2-methyl-, 1,1'-(1,4-butanediyl) ester							
Route of exposure	Result	Method	Exposure time	Species	Sex	Value determination	Source
Dermal	Sensitizing	OECD 429		Mouse	F	Experimentally	ECHA

methyl methacrylate							
Route of exposure	Result	Method	Exposure time	Species	Sex	Value determination	Source
Dermal	Sensitizing	OECD 429		Mouse		Observation method	ECHA
Inhalation	Not sensitizing						ECHA

VILLACRYL STC HOT LIQUID

Creation date 07th November 2023 Version 2.0
 Revision date

Germ cell mutagenicity

Based on available data the classification criteria are not met.

2-Propenoic acid, 2-methyl-, 1,1'-(1,4-butanediyl) ester							
Result	Method	Exposure time	Specific target organ	Species	Sex	Value determination	Source
Negative without metabolic activation, Negative with metabolic activation	OECD 473			Chinese hamster (Cricetulus barabensis)		Experimentally	ECHA
Negative	OECD 474			Mouse	F/M	Experimentally	ECHA

methyl methacrylate							
Result	Method	Exposure time	Specific target organ	Species	Sex	Value determination	Source
Negative	OECD 476		Lung fibroblast	Chinese hamster (Cricetulus barabensis)			ECHA
Negative	OECD 478	5 days (6 hour/day)	Male reproductive organs	Mouse	M		ECHA

Carcinogenicity

Based on available data the classification criteria are not met.

methyl methacrylate							
Route of exposure	Parameter	Value	Specific target organ	Result	Species	Sex	Source
Oral	NOAEL	90.3 mg/kg bw/day	Kidney	Not carcinogenic	Rat (Rattus norvegicus)	F/M	ECHA
Inhalation	NOAEC	2050 mg/m ³		Not carcinogenic	Rat (Rattus norvegicus)	F/M	ECHA

Reproductive toxicity

Based on available data the classification criteria are not met.

2-Propenoic acid, 2-methyl-, 1,1'-(1,4-butanediyl) ester								
Effect	Parameter	Method	Value	Result	Species	Sex	Value determination	Source
Effects on fertility	NOAEL	OECD 422	1000 mg/kg bw/day	No effect	Rat (Rattus norvegicus)	F/M	Experimentally	ECHA
Developmental toxicity	NOAEL	OECD 422	1000 mg/kg bw/day	Local effects	Rat (Rattus norvegicus)	F/M	Experimentally	ECHA

Toxicity for specific target organ - single exposure

May cause respiratory irritation.

Toxicity for specific target organ - repeated exposure

Based on available data the classification criteria are not met.

VILLACRYL STC HOT LIQUID

Creation date	07th November 2023	Version	2.0
Revision date			

Repeated dose toxicity

2-Propenoic acid, 2-methyl-, 1,1'-(1,4-butanediyl) ester								
Route of exposure	Parameter	Result	Method	Value	Exposure time	Species	Sex	Source
Oral	NOAEL		OECD 422	300 mg/kg bw/day		Rat (Sprague-Dawley)	F/M	ECHA

methyl methacrylate								
Route of exposure	Parameter	Result	Method	Value	Exposure time	Species	Sex	Source
Oral (drinking water)	NOAEL	No effect		124 mg/kg bw/day		Rat (Rattus norvegicus)	F/M	ECHA
Inhalation	NOAEC	No effect	OECD 453	2080 mg/m ³		Rat (Rattus norvegicus)	F/M	ECHA
Inhalation	NOAEC	Local effects		104 mg/m ³		Rat (Rattus norvegicus)		ECHA
Inhalation	LOEC	Local effects		416 mg/m ³		Rat (Rattus norvegicus)		ECHA

Aspiration hazard

Based on available data the classification criteria are not met.

More information

Metabolism, toxicokinetics, mechanism of action and other information: Data for mixture is not available. The product is mixture of methacrylic acid esters. According to literature data MMA and the other methacrylate esters are readily absorbed by all routes and rapidly hydrolyzed by carboxylesterases to methacrylic acid (MAA) and the respective alcohol. A rapid elimination of the substance is expected, mainly in urine, exhaled air (resulting from the conversion into acrylic acid and then into CO₂) and with feces. (ECHA Dossier)

11.2. Information on other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 12: Ecological information

12.1. Toxicity

Data not available.

Acute toxicity

2-Propenoic acid, 2-methyl-, 1,1'-(1,4-butanediyl) ester							
Parameter	Method	Value	Exposure time	Species	Environment	Value determination	Source
EC ₅₀		32.5 mg/l	48 hours	Fish (Golden olfe)	Fresh water	Experimentally	ECHA
NOEC		25 mg/l	48 hours	Fish (Golden olfe)	Fresh water	Experimentally	ECHA
LC ₅₀		12.4 mg/l	96 hours	Fish (Golden olfe)	Fresh water	Experimentally	ECHA
NOEC	OECD 201	2.11 mg/l	72 hours	Algae (Desmodesmus subspicatus)	Fresh water	Experimentally	ECHA
EC ₁₀	OECD 201	4.35 mg/l	72 hours	Algae (Desmodesmus subspicatus)	Fresh water	Experimentally	ECHA
EC ₅₀	OECD 201	9.79 mg/l	72 hours	Algae (Desmodesmus subspicatus)	Fresh water	Experimentally	ECHA

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

VILLACRYL STC HOT LIQUID

Creation date
Revision date

07th November 2023

Version

2.0

2-Propenoic acid, 2-methyl-, 1,1'-(1,4-butanediyl) ester

Parameter	Method	Value	Exposure time	Species	Environment	Value determination	Source
NOEC	OECD 310	20 mg/l	28 days	Other aquatic organisms	Fresh water	Experimentally	ECHA

methyl methacrylate

Parameter	Method	Value	Exposure time	Species	Environment	Value determination	Source
LC ₅₀	EPA OTS 797.1400	>79 mg/l	96 hours	Fish (Oncorhynchus mykiss)	Fresh water	Experimentally	ECHA
NOEC	EPA OTS 797.1400	40 mg/l	96 hours	Fish (Oncorhynchus mykiss)	Fresh water	Experimentally	ECHA
NOEC	EPA OTS 797.1300	48 mg/l	48 hours	Daphnia (Daphnia magna)	Fresh water	Experimentally	ECHA
EC ₅₀	EPA OTS 797.1300	69 mg/l	48 hours	Daphnia (Daphnia magna)	Fresh water	Experimentally	ECHA
EC ₅₀	OECD 201	>110 mg/kg	72 hours	Algae (Selenastrum capricornutum)	Fresh water	Experimentally	ECHA
NOEC	OECD 201	110 mg/kg	72 hours	Algae (Selenastrum capricornutum)	Fresh water	Experimentally	ECHA
NOEC	OECD 301C	100 mg/l	14 days	Microorganisms (Photobacterium phosphoreum)	Fresh water	Experimentally	ECHA

Chronic toxicity

2-Propenoic acid, 2-methyl-, 1,1'-(1,4-butanediyl) ester

Parameter	Method	Value	Exposure time	Species	Environment	Value determination	Source
NOEC	OECD 211	5.09 mg/l	21 days	Daphnia (Daphnia magna)	Fresh water	Experimentally	ECHA
LOEC	OECD 211	13.5 mg/l	21 days	Daphnia (Daphnia magna)	Fresh water	Experimentally	ECHA
EC ₁₀	OECD 211	7.51-15.5 mg/l	21 days	Daphnia (Daphnia magna)	Fresh water	Experimentally	ECHA
EC ₅₀	OECD 211	14.1-22.1 mg/l	21 days	Daphnia (Daphnia magna)	Fresh water	Experimentally	ECHA

methyl methacrylate

Parameter	Method	Value	Exposure time	Species	Environment	Value determination	Source
LOEC	OECD 210	18.8 mg/l	35 days	Fish (Danio rerio)	Fresh water	Experimentally	ECHA
NOEC	OECD 210	9.4 mg/l	35 days	Fish (Danio rerio)	Fresh water	Experimentally	ECHA
LC ₅₀	OECD 210	33.7 mg/l	35 days	Fish (Danio rerio)	Fresh water	Experimentally	ECHA

VILLACRYL STC HOT LIQUID

Creation date 07th November 2023
 Revision date Version 2.0

methyl methacrylate							
Parameter	Method	Value	Exposure time	Species	Environment	Value determination	Source
NOEC	OECD 211	37 mg/l	21 days	Daphnia (Daphnia magna)	Fresh water	Experimentally	ECHA
LOEC	OECD 211	68 mg/l	21 days	Daphnia (Daphnia magna)	Fresh water	Experimentally	ECHA
EC ₅₀	OECD 211	49 mg/l	21 days	Daphnia (Daphnia magna)	Fresh water	Experimentally	ECHA

More information

Avoid release to the environment.

12.2. Persistence and degradability

not available

Biodegradability

2-Propenoic acid, 2-methyl-, 1,1'-(1,4-butanediyl) ester							
Parameter	Method	Value	Exposure time	Environment	Value determination	Result	Source
% degradation (CO ₂ evolution)	OECD 310	84 %	28 days	Fresh water	Experimentally	Easily biodegradable	ECHA

methyl methacrylate							
Parameter	Method	Value	Exposure time	Environment	Value determination	Result	Source
% Degradation	OECD 301C	94 %	14 days	Fresh water	Experimentally	Easily biodegradable	ECHA

12.3. Bioaccumulative potential

Data not available.

12.4. Mobility in soil

Data not available.

12.5. Results of PBT and vPvB assessment

Product does not contain any substance meeting the criteria for PBT or vPvB in accordance with the Annex XIII of Regulation (EC) No 1907/2006 (REACH) as amended.

12.6. Endocrine disrupting properties

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

12.7. Other adverse effects

Data not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Proceed in accordance with valid regulations on waste disposal. Any unused product and contaminated packaging should be put in labelled containers for waste collection and submitted for disposal to a person authorised for waste removal (a specialized company) that is entitled for such activity. Do not empty unused product in drainage systems. The product must not be disposed of with municipal waste. Empty containers may be used at waste incinerators to produce energy or deposited in a dump with appropriate classification. Perfectly cleaned containers can be submitted for recycling.

VILLACRYL STC HOT LIQUID

Creation date	07th November 2023	Version	2.0
Revision date			

Waste management legislation

Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

Waste type code

16 03 03 inorganic wastes containing hazardous substances *

Packaging waste type code

15 01 10 packaging containing residues of or contaminated by hazardous substances *

(*) - Hazardous waste according to Directive 2008/98/EC on hazardous waste

SECTION 14: Transport information

14.1. UN number or ID number

UN 1247

14.2. UN proper shipping name

METHYL METHACRYLATE MONOMER, STABILIZED

14.3. Transport hazard class(es)

3 Flammable liquids

14.4. Packing group

II - substances presenting medium danger

14.5. Environmental hazards

not relevant

14.6. Special precautions for user

Reference in the Sections 4 to 8. Self-accelerating decomposition temperature (SAPT) >50oC

14.7. Maritime transport in bulk according to IMO instruments

not relevant

Additional information

Hazard identification No.	339
UN number	1247
Classification code	F1
Safety signs	3



Road transport - ADR

Special provisions	386
Limited quantities	1 L
Excepted quantities	E2

Packaging

Packing instructions	P001, IBC02, R001
Mixed packing provisions	MP19

Portable tanks and bulk containers

Guidelines	T4
Special provisions	TP1

ADR tank

Tank code	LGBF
Vehicles for tank carriage	FL
Transport category	4
Tunnel restriction code	(D/E)

Special provision for

packages operation	V8 S2, S4, S20
--------------------	-------------------

VILLACRYL STC HOT LIQUID

Creation date	07th November 2023	Version	2.0
Revision date			

Railway transport - RID

Special provisions	386
Excepted quantities	E2

Packaging

Packing instructions	P001, IBC02, R001
Mixed packing provisions	MP19

Portable tanks and bulk containers

Guidelines	T4
Special provisions	TP1

RID Tanks

Tank code	LGBF
Transport category	0

Special provision for

packages	W 8
----------	-----

Air transport - ICAO/IATA

Packaging instructions for limited amount	Y341
Packaging instructions passenger	353
Cargo packaging instructions	364

Marine transport - IMDG

EmS (emergency plan)	F-E, S-D
----------------------	----------

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Commission Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out (mixture).

SECTION 16: Other information

A list of standard risk phrases used in the safety data sheet

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.

Guidelines for safe handling used in the safety data sheet

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing mist/vapours/spray.
P264	Wash hands and exposed parts of the body thoroughly after handling.
P280	Wear protective gloves.
P370+P378	In case of fire: Use powder extinguisher/sand/carbon dioxide to extinguish.
P403+P235	Store in a well-ventilated place. Keep cool.

Other important information about human health protection

The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1. The user is responsible for adherence to all related health protection regulations.

Key to abbreviations and acronyms used in the safety data sheet

ADR	European agreement concerning the international carriage of dangerous goods by road
-----	---

VILLACRYL STC HOT LIQUID

Creation date	07th November 2023	Version	2.0
Revision date			

BCF	Bioconcentration Factor
CAS	Chemical Abstracts Service
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substance and mixtures
EC	Identification code for each substance listed in EINECS
EC ₁₀	Concentration of a substance when it is affected 10% of the population
EC ₅₀	Concentration of a substance when it is affected 50% of the population
EINECS	European Inventory of Existing Commercial Chemical Substances
EmS	Emergency plan
EU	European Union
EuPCS	European Product Categorisation System
IATA	International Air Transport Association
IBC	International Code For The Construction And Equipment of Ships Carrying Dangerous Chemicals
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
IMO	International Maritime Organization
INCI	International Nomenclature of Cosmetic Ingredients
ISO	International Organization for Standardization
IUPAC	International Union of Pure and Applied Chemistry
LC ₅₀	Lethal concentration of a substance in which it can be expected death of 50% of the population
LD ₅₀	Lethal dose of a substance in which it can be expected death of 50% of the population
log K _{ow}	Octanol-water partition coefficient
NOAEC	No observed adverse effect concentration
NOAEL	No observed adverse effect level
NOEC	No observed effect concentration
OEL	Occupational Exposure Limits
PBT	Persistent, Bioaccumulative and Toxic
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Agreement on the transport of dangerous goods by rail
UN	Four-figure identification number of the substance or article taken from the UN Model Regulations
UVCB	Substances of unknown or variable composition, complex reaction products or biological materials
VOC	Volatile organic compounds
vPvB	Very Persistent and very Bioaccumulative
Eye Irrit.	Eye irritation
Flam. Liq.	Flammable liquid
Skin Irrit.	Skin irritation
Skin Sens.	Skin sensitization
STOT SE	Specific target organ toxicity - single exposure

Training guidelines

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

Recommended restrictions of use

not available

Information about data sources used to compile the Safety Data Sheet

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended.
REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

The changes (which information has been added, deleted or modified)

Version 2.0 replaces the SDS version from 05/18/2021. Data updates and changes have been made to all sections of the SDS.

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

VILLACRYL STC HOT LIQUID

Creation date	07th November 2023	Version	2.0
Revision date			

More information

Classification procedure - calculation method.

Statement

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.